

BSTZ No. 06259P005
Express Mail No. EV323394176US

UNITED STATES PATENT APPLICATION

FOR

A SYSTEM AND METHOD FOR CENTRALIZED STATION MANAGEMENT

Inventor:

Pradeep J. Iyer
Partha Narasimhan
Merwyn Andrade
John Taylor

Prepared by:

Blakely, Sokoloff, Taylor & Zafman LLP
12400 Wilshire Boulevard, Suite 700
Los Angeles, California 90025
(714) 557-3800

A SYSTEM AND METHOD FOR CENTRALIZED STATION MANAGEMENT

FIELD

[001] Embodiments of the invention relate to the field of wireless communications, in particular, to a centralized mechanism for managing operations of and communications within a wireless network.

GENERAL BACKGROUND

[002] Over the last decade or so, businesses have begun to install enterprise networks with one or more local area networks in order to allow their employees to share data and improve work efficiency. To further improve work efficiency, various enhancements have added to local area networks. One enhancement is remote wireless access, which provides an important extension in forming a wireless local area network (WLAN).

[003] A WLAN supports communications between wireless stations (STAs) and Access Points (APs). Normally, each AP independently operates as a relay station by supporting communications between wireless stations of a wireless network and resources of a wired network. Hence, the APs are designed to operate autonomously, with each AP maintaining sufficient intelligence to control its own connections with STAs. As a result, conventional WLANs are subject to a number of disadvantages.

[004] For instance, conventional WLANs are unable to effectively respond to man-in-the-middle attacks, especially where the attacker impersonates an AP by sending deauthentication messages to a targeted STA. Moreover, since each AP is designed to operate autonomously, the network administrator needs to separately configure

individual APs, a major undertaking when a large number of APs are required in order to provide complete coverage at a site.

BRIEF DESCRIPTION OF THE DRAWINGS

[005] The invention may best be understood by referring to the following description and accompanying drawings that are used to illustrate embodiments of the invention.

[006] Figure 1 is an exemplary embodiment of a wireless network in accordance with the invention.

[007] Figure 2 is an exemplary embodiment of a wireless network switch of Figure 1.

[008] Figure 3A is an exemplary embodiment of the wireless network switch operating in cooperation with an Access Point (AP) to respond to a security attack on a wireless station (STA) of the wireless network.

[009] Figure 3B is an exemplary embodiment of the operations of station management logic for a wireless network switch to block communications by a station under a security attack.

[0010] Figure 4 is an exemplary embodiment of a method of operation of the wireless network switch responding to a security attack.

[0011] Figure 5 is an exemplary embodiment of the wireless network switch operating in cooperation with a wireless station (STA) for centralized load balancing for the wireless network.

[0012] Figure 6 is an exemplary embodiment of a method of operation of the wireless network switch for load balancing.

[0013] Figure 7 is an exemplary embodiment of a wireless network switch operating in cooperation with an Access Point (AP) to detect coverage holes over a site.

[0014] Figure 8 is an exemplary embodiment of a method of operation of the wireless network switch for detecting coverage holes.

[0015] Figure 9 is an exemplary embodiment of a method of operation of the wireless network switch for limiting broadcast and/or multicast traffic over an Access Point (AP).

[0016] Figure 10 is an exemplary embodiment of a method of operation of the wireless network switch for RF neighborhood detection.

DETAILED DESCRIPTION

[0017] Embodiments of the invention relate to a centralized mechanism for managing operations of and communications within a wireless network. According to one illustrative embodiment, the centralized mechanism may be deployed as station management logic (STM) within a wireless network switch. This logic may be deployed as a software module, executed by a processor, that is configured to handle the processing of a plurality of management messages during an Association phase between a STA and an AP, including but not limited or restricted to one or more of the following: PROBE REQUEST, PROBE RESPONSE, AUTHENTICATION, DEAUTHENTICATION, ASSOCIATION REQUEST, ASSOCIATION RESPONSE, REASSOCIATION REQUEST, REASSOCIATION RESPONSE and DISASSOCIATION. Moreover, the station management logic (STM) is configured to provide security protection, load balancing, coverage hole detection, and broadcast/multicast traffic reduction.

[0018] Herein, the invention may be applicable to a variety of wireless networks such as a wireless local area network (WLAN) or wireless personal area network (WPAN). The wireless network may be configured in accordance with any wireless communication protocol. Examples of various types of wireless communication protocols include Institute of Electrical and Electronics Engineers (IEEE) 802.11 standards, High Performance Radio Local Area Networks (HiperLAN) standards, WiMax (IEEE 802.16) and the like. For instance, the IEEE 802.11 standard may an IEEE 802.11b standard entitled "Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications: Higher-Speed Physical Layer Extension in the 2.4 GHz Band" (IEEE 802.11b, 1999); an IEEE 802.11a standard entitled "Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY)

specifications: High-Speed Physical Layer in the 5 GHz Band" (IEEE 802.11a, 1999); a revised IEEE 802.11 standard "Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications" (IEEE 802.11, 1999); or an IEEE 802.11g standard entitled "Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications: Further Higher Data Rate Extension in the 2.4 GHz Band" (IEEE 802.11g, 2003).

[0019] Certain details are set forth below in order to provide a thorough understanding of various embodiments of the invention, albeit the invention may be practiced through many embodiments other than those illustrated. Well-known logic and operations are not set forth in detail in order to avoid unnecessarily obscuring this description.

[0020] In the following description, certain terminology is used to describe features of the invention. For example, "logic" includes hardware and/or software module(s) that are configured to perform one or more functions. For instance, a "processor" is logic that processes information. Examples of a processor include a microprocessor, an application specific integrated circuit, a digital signal processor, a micro-controller, a finite state machine, or even combinatorial logic.

[0021] A "software module" is executable code such as an operating system, an application, an applet or even a routine. Software modules may be stored in any type of memory, namely suitable storage medium such as a programmable electronic circuit, a semiconductor memory device, a volatile memory (e.g., random access memory, etc.), a non-volatile memory (e.g., read-only memory, flash memory, etc.), a floppy diskette, an optical disk (e.g.,

compact disk or digital versatile disc "DVD"), a hard drive disk, tape, or any kind of interconnect (defined below).

[0022] An "interconnect" is generally defined as an information-carrying medium that establishes a communication pathway. The interconnect may be a wired interconnect, where the medium is a physical medium (e.g., electrical wire, optical fiber, cable, bus traces, etc.) or a wireless interconnect (e.g., air in combination with wireless signaling technology).

[0023] "Information" is defined as data, address, control or any combination thereof. For transmission, information may be transmitted as a message, namely a collection of bits in a predetermined format. One particular type of message is a frame including a header and a payload, each having a predetermined number of bits of information.

[0024] I. General Architecture

[0025] Referring to Figure 1, an exemplary embodiment of a wireless network 100 having a centralized mechanism to manage the operations of and communications within wireless network 100 is illustrated. According to this embodiment of the invention, wireless network 100 is deployed as a wireless local area network (WLAN) that comprises one or more wireless network switches 110 (e.g., WLAN switch) in communication with one or more access points (APs) 130_1 - 130_N (where $N \geq 1$) over an interconnect 120. Interconnect 120 may be a wired or wireless information-carrying medium or even a mesh network for example. In addition, one or more wireless stations (STAs) 140_1 - 140_M ($M \geq 1$) are in communication with APs 130_1 - 130_N over wireless interconnects 150.

[0026] As shown in Figures 1 and 2, WLAN switch 110 comprises logic 200 that supports communications with APs

130₁-130_N over interconnect 120. Moreover, the wired network features resources that are available for users of wireless network 100. Such resources may include database or data storage servers.

[0027] WLAN switch 110 supports bi-directional communications by receiving messages from and transmitting messages to one or more targeted APs 130₁,..., 130_N over interconnect 120. Interconnect 120 may be part of any type of private or public wired network, including but not limited or restricted to Ethernet, Token Ring, Asynchronous Transfer Mode (ATM), Internet or the like. The network communication protocol utilized over interconnect 120 may be selected from a variety of protocols, including TCP/IP.

[0028] More specifically, logic 200 of WLAN switch 110 comprises station management logic (STM) 210 and a wired or wireless connector 220. Connector 220 enables an exchange of information between a wired network and station management logic 210. For instance, connector 220 may provide coupling for a plurality of Ethernet interconnects, serial interconnects and the like to enable access with APs over a wired public or private network.

[0029] Herein, station management logic 210 processes information extracted from the wireless message. According to one embodiment of the invention, station management logic 210 is implemented as a processor executing a program, stored in memory, that is configured to provide centralized management involving security protection, load balancing, coverage hole detection, and broadcast/multicast traffic reduction of wireless network 100. Alternatively, station management logic 210 may be a state machine. Regardless of the chosen architectural implementation, in order to provide

such centralized management, different information is received, extracted and processed as described below.

[0030] Referring back to Figure 1, each AP 130₁, ..., or 130_N supports bi-directional communications by receiving wireless messages from any or all of the STAs 140₁-140_M in its coverage area and transferring data from the messages over interconnect 120 to which WLAN switch 110 is coupled.

[0031] STA 140₁ is adapted to communicate with and accesses information from any associated AP. For instance, STA 140₁ is associated with AP 130₁ and communicates over the air in accordance with a selected wireless communications protocol. Hence, AP 130₁ generally operates as a transparent bridge connecting both wireless network 100 featuring STA 140₁ with the wired network.

[0032] According to one embodiment, STA 140₁ comprises a removable, wireless network interface card (NIC) that is separate from or employed within a wireless device that processes information (e.g., computer, personal digital assistant "PDA", telephone, alphanumeric pager, etc.). Normally, the NIC comprises a wireless transceiver, although it is contemplated that the NIC may feature only receive (RX) or transmit (TX) functionality such that only a receiver or transmitter is implemented.

[0033] II. General Centralized Management operations

A. SECURITY .

[0034] Referring now to Figure 3A, an exemplary embodiment of a wireless network switch (e.g., WLAN switch 110) operating in cooperation with one or more access points (e.g., AP 130₁) to respond to a security attack on a wireless station (STA 140₁) is shown. One common security attack is a "man-in-the-middle" attack that involves an

attacker assuming the identity of an AP or STA and sending DEAUTHENTICATION messages to the other. This disrupts communications between AP 130₁ and STA 140₁ so that the attacker can monitor ("sniff") for passwords and other information as communication is reestablished.

[0035] Since message headers (e.g., IEEE 802.11 headers) are not encrypted, the attacker can obtain Media Access Control (MAC) addresses for both AP 130₁ and STA 140₁. While it is easy to prevent a man-in-the-middle attack against AP 130₁, it is difficult to prevent such attacks against STA 140₁, which is beyond the control of AP 130₁. Centralized station management deployed within WLAN switch 110 allows more effective solution to curtail the man-in-the-middle attack.

[0036] Herein, STA 140₁ receives a DEAUTHENTICATION message 300 that impersonates origination from AP 130₁. However, since STA 140₁ is in the coverage area for AP 130₁, AP 130₁ detects DEAUTHENTICATION message 300 and forwarded the same to WLAN switch 110 for processing. Upon analysis of the type and subtype fields 310 of DEAUTHENTICATION message 300, WLAN switch 110 is able to determine that a DEAUTHENTICATION message has been received.

[0037] In particular, during normal operations, WLAN switch 110 is responsible for generating all valid DEAUTHENTICATION messages to STAs. Hence, according to one embodiment of the invention, station management software executed within WLAN switch 110 is able to immediately determine whether DEAUTHENTICATION message 300 is invalid through analysis of a source address (SRC_ADDR) 320 and/or destination address (DEST_ADDR) 330.

[0038] For instance, according to one embodiment of the invention, if DEST_ADDR 330 indicates that the STA 140₁ is

the targeted device, but WLAN switch 110 has no record of generating DEAUTHENTICATION message 300, DEAUTHENTICATION message 300 is deemed invalid. Namely, DEST_ADDR 330 of DEAUTHENTICATION message 300 is compared to corresponding information from all valid DEAUTHENTICATION messages recently transmitted from WLAN switch 110. Data associated with recent, valid DEAUTHENTICATION messages are stored within a table accessible by WLAN switch 110. If no match is detected, DEAUTHENTICATION message 300 is invalid. This causes WLAN switch 110 to block communications generated by STA 140₁ for associating with any AP 130₁,... or 130_N.

[0039] According to one embodiment of the invention, as shown in Figure 3B, WLAN switch 110 places the MAC address of STA 140₁ into a security table 340. Thereafter, WLAN switch 110 sends a message to an AP (e.g., AP 130₂), to which STA 140₁ is currently associated, to disassociate itself from STA 140₁. Thereafter, upon receipt of any PROBE REQUEST, ASSOCIATION REQUEST or REASSOCIATION REQUEST messages transferred any AP 130₁,... or 130_N in wireless network 100, WLAN switch 110 accesses security table 340 to determine whether the station initiating the request message, such as STA 140₁, is blocked. This may be accomplished by comparison of the SRC_ADDR of the request message to contents of security table 340 as shown.

[0040] If the station initiating the request is blocked, the request message is denied. STA 140₁ may be precluded from freely communicating with any APs 130₁-130_N of wireless network 100 for either (i) a prescribed time period, which may be static or programmable for each network, or (ii) an indefinite duration until the network administrator removes STA 140₁ from security table 340.

[0041] Referring to Figure 4, an exemplary embodiment of a method of operation of a wireless network switch, such as a WLAN switch for example, responding to a security attack is shown. First, within its coverage area, an AP monitors the airwaves within its coverage area for broadcast, multicast and addressed wireless messages (item 400). For each received wireless message, the AP determines the particular type of wireless message received (item 410). This is accomplished by analyzing a message (or frame) type field in the header of the message. Upon determining a detected wireless message is a management message, such as a DEAUTHENTICATION message for example, the AP forwards the DEAUTHENTICATION message to the station management logic of the wireless network switch (items 420 and 425).

[0042] During normal operations, the station management logic generates all valid DEAUTHENTICATION messages to STAs. Upon receipt of the DEAUTHENTICATION message, which has been generated by a device other than the wireless network switch, the station management logic knows that a targeted STA is being attacked by reviewing of the DEST_ADDR of DEAUTHENTICATION message with records of recently generated DEAUTHENTICATION messages for example (item 430). This causes the station management logic to continuously block requests made by the targeted STA (item 440). These requests include a PROBE REQUEST, an ASSOCIATION REQUEST, a REASSOCIATION REQUEST and the like.

[0043] According to one embodiment of the invention, requests from the targeted STA are blocked by the station management logic monitoring for management messages from the targeted STA (e.g., analyzing source address of a PROBE REQUEST, ASSOCIATION REQUEST, or REASSOCIATION REQUEST). Upon discovery, station management logic generates a message to the AP to deny such request.

[0044] After it is no longer necessary to block requests from the targeted STA, the targeted STA is permitted by the station management logic to freely associate with any AP (blocks 450 and 460). Such blocking may be lifted by the station management logic if (1) the network administrator manually clears the targeted STA from a block list, or (2) a prescribed time period for blocking requests by STA has elapsed. The prescribed time may automatically elapse if based on a policy rule established by the network administrator.

B. LOAD BALANCING

[0045] Referring now to Figure 5, an exemplary embodiment of wireless network switch 110 operating in cooperation with one or more access points (e.g., AP 130₁, AP 130₂, AP 130₃) and a wireless station (STA 140₁) attempting to associate with one of the APs 130₁-130₃ is shown. In particular, station management logic 210 of wireless network switch 110 provides centralized control in steering STA 140₁ to a suitable AP during the Association phase.

[0046] STA 140₁ is configured to associate with an AP through passive scanning (beacons) or active scanning. "Active scanning" involves STA 140₁ broadcasting a PROBE REQUEST message 500 to all APs capable of receiving the request on multiple channels. For this embodiment, APs 130₁-130₃ receive a first PROBE REQUEST message 500. However, instead of each AP 130₁-130₃ returning a response to STA 140₁, first PROBE REQUEST message 500 is altered and subsequently routed to station management logic 210.

[0047] More specifically, upon receipt of first PROBE REQUEST message 500, each AP 130₁-130₃ measures the received signal strength for first PROBE REQUEST message 500 and generates a corresponding received signal strength indicator

(RSSI) value 510_1-510_3 . At each AP 130_1-130_3 , the RSSI value 510_1-510_3 is loaded into a field 520 of first PROBE REQUEST 500 (e.g., Duration ID field) to produce modified Probe Requests 530_1-530_3 , respectively. Thereafter, modified Probe Request messages 530_1-530_3 are transferred to station management logic 210 from AP 130_1-130_3 , respectively. At this time, station management logic (STM) 210 does not respond to modified Probe Request messages 530_1-530_3 , but rather awaits a second set of Probe Request messages 550_1-550_3 or modified versions thereof.

[0048] As shown, in response to a second PROBE REQUEST message 540, AP 130_1-130_3 collectively route the second set of Probe Request messages 550_1-550_3 to station management logic 210. It is contemplated that Probe Request messages 550_1-550_3 may be modified to include the newly measured RSSI value. However, if the time duration between first PROBE REQUEST 500 and second PROBE REQUEST message 540 is nominal (e.g., a few milliseconds), modified Probe Request messages 550_1-550_3 need not include an updated RSSI value.

[0049] It is contemplated that additional parameters, such as (i) number of users on AP 130_1-130_3 or (ii) percentage of bandwidth utilization by AP 130_1-130_3 for example, may be monitored by the AP themselves and periodically transferred to wireless network switch 110. In this type of embodiment, the values of these parameters may be contained in fields of the first or second set of modified Probe Request messages 530_1-530_3 or 550_1-550_3 , respectively. However, the number of users on AP 130_1-130_3 and/or the percentage of bandwidth utilization by AP 130_1-130_3 may be monitored by wireless network switch 110 internally, where load balancing is activated when maximum or minimum thresholds are exceeded.

[0050] At this time, STM 210 analyzes the RSSI values and/or load on each AP, and responds to second PROBE REQUEST message 540 on behalf of the AP 130₁,..., or 130₃ selected to associate with STA 140₁ (e.g., AP 130₁). This allows STM 210 to steer STA 140₁ to a suitable AP based on instantaneous load and proximity. Moreover, by ignoring an initial PROBE REQUEST by STA 140₁, this centralized Request/Response processing allows overloaded APs and/or APs remotely located from the STA to be hidden during the Association phase.

[0051] After PROBE RESPONSE message 560 has been received, STA 140₁ starts the authentication and associate exchanges with the selected AP 130₁. Thereafter, communications are established between STA 140₁ and AP 130₁.

[0052] Figure 6 is an exemplary embodiment of a method of operation of the wireless network switch for load balancing during an initial communication session. For this embodiment of the invention, STA sends a PROBE REQUEST message in an attempt to associate with an AP (item 600). The PROBE REQUEST message is usually sent to a broadcast address so that multiple APs can receive the PROBE REQUEST message. Upon receipt, each AP computes the RSSI value for the received PROBE REQUEST message (item 610). The RSSI value may be placed in an unused field of the PROBE REQUEST message for transfer to the STM (item 620). Of course, as shown as an optional operation in item 630, other parameter values may be placed in unused field(s) of the PROBE REQUEST message such as load on the AP (e.g., number of users, percentage of bandwidth utilized, etc.). Thereafter, the modified PROBE REQUEST messages are transferred to the STM of the wireless network switch (item 640).

[0053] Alternatively, in lieu of sending modified versions of the received PROBE REQUEST message as described above,

each AP may be configured to send a message other than a modified PROBE REQUEST message. This message would be inclusive of the RSSI value and only selected information from the received PROBE REQUEST message. For instance, the selected information may include (i) a code to identify that the message is a PROBE REQUEST message, (ii) an address of the STA generating the PROBE REQUEST message, (iii) load of the AP, etc.

[0054] Upon receipt of messages from the APs, generated in response to receipt of the PROBE REQUEST, the STM does not respond, but rather awaits a second set of messages produced in response to another (second) PROBE REQUEST message generated by the STA when the previous (first) PROBE REQUEST message was not responded to (items 650 and 660). The second set of messages may be modified PROBE REQUEST messages including newly measured RSSI value and/or load information). However, if the time duration between the first PROBE REQUEST message and second PROBE REQUEST message is nominal (e.g., a few milliseconds), the second set of messages may be identical to the subsequent (second) PROBE REQUEST message or may be modified to include other information needed to determine the optimal AP to associate with the STA.

[0055] After receipt of the second set of messages, the STM analyzes the RSSI values and/or load on each AP, and responds to second PROBE REQUEST message on behalf of the AP selected to associate with STA (items 670, 680 and 690). By the station management logic hiding overloaded APs and/or APs remotely located from the STA during the Association phase, the overall wireless traffic is substantially reduced.

C. COVERAGE HOLE DETECTION

[0056] Referring now to Figure 7, an exemplary embodiment of a wireless network switch operating in cooperation with an Access Point (AP) to detect coverage holes over a wireless network 100 is shown. A "coverage hole" is a location where a STA cannot associate with any AP. Centralized station management logic allows for the wireless network to discover coverage holes and to automatically perform events to eliminate or substantially reduce discovered coverage holes. Examples of such events include, but are not limited or restricted to (1) increasing transmission power for selected APs or (2) notifying a network administrator regarding the coverage hole.

[0057] As shown in Figure 7, wireless network 100 comprises wireless network switch 110, one or more access points (e.g., AP 130₁, ..., AP 130_N) and one or more wireless stations (e.g., STA 140₁). Station management logic (STM) 210, implemented within wireless network switch 110, provides centralized control for management messages received from each AP 130₁-130_N during an Association phase with STA 140₁. In particular, each AP 130₁-130_N measures the RSSI value for a received management frame 700 and provides the RSSI value to STM 210.

[0058] According to this embodiment, two RSSI thresholds are used to determine the presence of a coverage hole. These thresholds may be static in nature (e.g., set in one-time programmable memory of wireless network switch 110) or may be dynamic in nature (e.g., set by a network administrator in memory of wireless network switch 110). A first RSSI threshold (referred to as "Good_RSSI_Threshold") indicates that STA 140₁ is not in a coverage hole if any AP 130₁, ..., or 130_N detects an RSSI value more than Good_RSSI_Threshold for

any message from STA 140₁. A second RSSI threshold (referred to as "Bad_RSSI_Threshold") indicates that that STA 140₁ may be in a coverage hole if all APs 130₁-130_N detect an RSSI value below Bad_RSSI_Threshold during message broadcasts from STA 140₁ during the Association phase. As illustrative examples, Good_RSSI_Threshold may be set to approximately 20 dbm0 while Bad_RSSI_Threshold may be set to approximately 10 dbm0.

[0059] In summary, during the Association phase, wireless communications by STA 140₁ are monitored. If none of APs 130₁-130_N detects an RSSI value for a management message above Bad_RSSI_Threshold, STM 210 adds STA 140₁ to a potential coverage hole list. Thereafter, if STA 140₁ either fails to complete association with an AP or consistently provides messages with RSSI values below Bad_RSSI_Threshold to the associated AP, STA 140₁ is determined to be in a coverage hole. Namely, the placement of STA 140₁ within an entry of the potential coverage hole list causes STM 210 to perform events to mitigate or eliminate the potential coverage hole.

[0060] Upon receiving a management frame, which originates from STA 140₁ and indicates an RSSI value above Good_RSSI_Threshold, STM 210 removes STA 140₁ from an entry of the potential coverage hole list.

[0061] Referring to Figure 8, an exemplary embodiment of a method of operation of the wireless network switch for detecting coverage holes is shown. Initially, a plurality of RSSI thresholds are established (item 800). These "thresholds," namely Good_RSSI_Threshold and Bad_RSSI_Threshold, are used to determine the presence of a coverage hole. Upon receipt of broadcasted management frames from the monitored STA, each AP measures the RSSI

value for the management frame and provides the RSSI value to the station management logic "STM" (items 810, 820 and 830). Based on the RSSI values from the APs, the STM determines whether any of these RSSI values are greater than Good_RSSI_Threshold (item 840). If so, there is no coverage hole at the location of the monitored STA (item 850).

[0062] Furthermore, based on the RSSI values from the APs, the station management logic determines whether all of the APs detect an RSSI value below Bad_RSSI_Threshold (item 860). If so, the station management logic adds the monitored STA to a potential coverage hole list (item 870). Thereafter, if the monitored STA either fails to complete association with an AP or consistently provides messages with RSSI values below Bad_RSSI_Threshold to the associated AP, the monitored STA is determined to be in a coverage hole (items 875 and 880). This causes the station management logic to initiate events to mitigate or eliminate such coverage holes (item 890).

D. BROADCAST & MULTICAST TRAFFIC REDUCTION

[0063] Referring to Figure 9, an exemplary embodiment of a method of operation of the wireless network switch for limiting broadcast and/or multicast traffic over an AP is shown. Herein, station management logic (STM) 210 has knowledge of all STAs 140_1 - 140_M associated with all APs 130_1 - 130_N in wireless network 100. Namely, STM 210 maintains an AP-STA table 900 to identify which STAs are associated with which APs. According to one embodiment, AP-STA table 900 comprises MAC addresses 910 for APs 130_1 - 130_N and MAC addresses 920 of STAs $140_1, \dots$, and/or 140_j associated with each AP $130_1, \dots$, or 130_N .

[0064] According to one embodiment of the invention, after a STA associates or disassociates with an AP, AP-STA table 900

is updated. Herein, the MAC address for the newly associated STA is added to AP-STA table 900 after the Association phase has completed. Likewise, a newly disassociated STA is removed from AP-STA table 900.

[0065] In addition, after an update, STM 210 determines whether an AP (e.g., AP 130₂) now has no STAs associated therewith. If so, STM 210 removes the MAC address of AP 130₂ from a multicast group list 930 stored within wireless network switch 110. Since multicast group list 930 is accessed by wireless network switch 110 to determine the targeted destinations for multicast and broadcast transmissions, AP 130₂ would discontinue sending any broadcast or multicast messages until at least one STA becomes associated with AP 130₂. Once a STA becomes associated with AP 130₂, STM 210 adds the MAC address of AP 130₂ back to multicast group list 930.

E. RF NEIGHBORHOOD DETECTION

[0066] Referring to Figure 10, an exemplary embodiment of a method of operation of the wireless network switch for RF neighborhood detection is shown. According to one embodiment of the invention, a wireless network switch receives PROBE REQUEST messages on different channels through different APs (1000). These PROBE REQUEST messages originate from the same STA.

[0067] Upon receipt, the wireless network switch dynamically computes RF neighborhoods of all APs deployed (1010). According to one embodiment of the invention, a channel number and a MAC address associated with the AP is included as information within the PROBE REQUEST message (1020). The wireless network switch creates a filtered channel list, which includes the MAC address of the AP and channel number extracted from PROBE REQUEST messages (1030). The filtered

channel list is provided to the STA at completion of its association, such as in an ASSOCIATION RESPONSE message for example (1040). This enables the STA to use this filtered channel list to make more efficient mobility decision in future associations.

[0068] While the invention has been described in terms of several embodiments, the invention should not be limited to only those embodiments described, but can be practiced with modification and alteration within the spirit and scope of the appended claims. The description is thus to be regarded as illustrative instead of limiting.